



Surveillance Camera TP-Link TL-SC3130G

Hersteller: TP-Link
Herstellerbez.: TL-SC3130G
Verpackung: Retail

Teilenummer: 75380001

Product Description:

The TL-SC3130G surveillance camera is a versatile solution for your home and office monitoring, whose 54Mbps wireless connectivity enables you to deploy the camera where inaccessible previously by Ethernet connection such as ceiling and walls.

This camera can be placed in your living room, office, or anywhere else you would like to keep an eye on things. After a hassle-free installation, you can view and control the camera from a Web browser, bundled software, or compatible cell phone.

Besides basic monitoring tools such as motion detection and E-mail alerts which is motion triggered sending an alert when the camera detects movement, advanced features of high availability are also added, such as 2-way audio, dual streaming, and 3GPP compatibility, even the error detection tool "Ping Watch Dog", making TL-SC3130G an excellent indoor surveillance solution.

Software Specification:

Standards and Protocols: Bonjour, TCP/IP, DHCP, PPPoE, ARP, ICMP, FTP, SMTP, DNS, NTP, UPnP, RTSP, RTP, HTTP, TCP,UDP, 3GPP/ISMA RTSP

Wireless Data Rates: Up to 54Mbps

Wireless Security: WPA-/WPA2-PSK,WPA-/WPA2-AES,WEP

Video compression: Motion JPEG; MPEG- 4 Part 2 (ISO/IEC 14496-2), Profile: SP

Frame rate & Resolutions: Up to 30 fps at 640x480, 320x240, 160x120

Video streaming: Simultaneous Motion JPEG and MPEG-4 (Dual streaming)

Security: Multiple user access levels with password protection, HTTPS encryption

Alarm and Event Management: Events triggered by motion detection and Schedule; Notification over TCP, email, HTTP

Bundled Management Software: Viewing and recording up to 16 cameras

Image settings:

Rotation: Mirror, Flip, Mirror Flip, brightness, contrast, saturation, hue

Overlay capabilities: time, date, text and privacy image

Audio: Two-way (full duplex); External microphone input

Audio compression: G.711 PCM, 8 kHz, 64 kbit/s

Users: 5 simultaneous users; Unlimited number of users using multicast

Minimum web browsing requirements: Pentium4 1.8GHz (or equivalent AMD); 64MB RAMgraphic cards; (or equivalent on-board graphic cards); 512MB RAM; Windows 98,ME, 2000, 2003, XP, Vista; Mac OS Leopard 10.5



Hardware Specification:

Interfaces: RJ-45 for Ethernet 10/100 Base-T; DC power jack; Reset push switch; 3.5mm jack for line out

Image sensor: 1/4" Progressive scan CMOS sensor

Lens: F2.0, 4.0mm

Digital zoom: 10x Digital

Min Illumination: 0.5 Lux

Safety & Emission: FCC, CE

Dimensions (HxWxD): 3.7 x 2.7 x 1.2 in. (96 x 58 x 31 mm)

Environment:

Operating Temperature: 0°C~40°C (32°F~104°F)

Storage Temperature: -40°C~70°C (-40°F~158°F)

Operating Humidity: 10%~90% non-condensing

Storage Humidity: 5%~90% non-condensing

Power : 5V DC, 2A